



Scan to see a full specifications, installation and agency certification information.

### APPLICATIONS:

APPLIANCE | ELECTRICAL | HVAC/R | MARINE | POOL & SPA | RV



### REPLACES

- **Field Controls:** 46144700
- **Gemline:** 1C216
- **Mars:** 32393

### FEATURES

- ✓ UL 873 recognition for compressor applications
- ✓ Post-purge fan delay timer
- ✓ OFF delay purges ducts of residual air at the end of the heating/cooling cycle
- ✓ Interrogation delay eliminates nuisance trips due to thermostat bounce/tampering

### OVERVIEW

Power must be applied before and during the time delay period. When the initiate contact closes, the load energizes and remains energized as long as the initiate contact is closed. The time delay begins when the initiate contact opens. At the end of the time delay period, the load is turned off. If the initiate contact recloses during the time delay period, the load remains energized and the time delay is reset to zero. Removal of the input power during the delay turns off the load and resets the time delay to zero. A one-second interrogation delay is provided to avoid nuisance trips due to thermostat bounce or tampering.

### SPECIFICATIONS

- **Voltage:** 18-30 VAC, 1 amp maximum, 40 mA, 10 amp inrush
- **Adjustable time delay:** OFF, 12-390 seconds

Content and specifications on sell sheets subject to change without notice.