



i3[®] SERIES Touch Thermostats

7-Day Programmable

INNOVATIVE • INTUITIVE • IMAGINATIVE

Through innovation, comes affordability!



Designed around capacitive touch sensing technology, the new and innovative i3 Series Touch Thermostats from ICM Controls feature huge displays and a patent-pending dynamic interface for intuitive programming that uses familiar icons that illuminate only when they are needed – all for an amazingly affordable price!



Features:

- **Large Display** – The touch icons are positioned away from the display for a larger viewing area; keeps display clean of fingerprints
- **Button/Switch Free Front** – No mechanical buttons or switches to break or wear
- **Dynamic Interface** – Highly intuitive – patent-pending! Icons illuminate ONLY when they are needed
- **Customized Printed Interface** – Color and plastic can be customized
- **Customized Icons** – Uses branded icons, or those found on most cell phones, in any desired backlit color
- **Humidity Control** – Humidity Control models available
- **Positioning** – Thin profile ideal for either “internal” or “wall mount” applications
- **Mounting Base** – Designed with sub base to make installation a “snap”
- **Removable Logo Plate** – Great for customers to promote their business
- **Wi-Fi** – Wi-Fi compatible models available with user friendly connectivity
- **Thermal Safety** – Excessive heating bi-metal safety switch
- **User Coded Lockout** – Designed with renters and children in mind





i3 Standard Thermostats

P/N	PROGRAM	STAGES	HP	POWER	WI-FI	HUMIDITY	TERMINATIONS
i1010R	7-Day	1H/1C	Y	Dual	N	N	RC, RH, C, W1/O/B, Y1, G, S1, S2, SC
i2010R	7-Day	2H/1C	Y	Dual	N	N	RC, RH, C, W1/O/B, W2, Y1, G, S1, S2, SC
i2020R	7-Day	2H/2C	Y	Dual	N	N	RC, RH, C, W1/O/B, W2, Y1, Y2, G, S1, S2, SC
i3020R	7-Day	3H/2C	Y	Dual	N	N	RC, RH, C, W1/O/B, W2, AUX, Y1, Y2, G, S1, S2, SC

i3 Wi-Fi Thermostats

P/N	PROGRAM	STAGES	HP	POWER	WI-FI	HUMIDITY	TERMINATIONS
i1010WR	7-Day	1H/1C	Y	Hardwired	Y	N	RC, RH, C, W1/O/B, Y1, G, S1, S2, SC
i2010WR	7-Day	2H/1C	Y	Hardwired	Y	N	RC, RH, C, W1/O/B, W2, Y1, G, S1, S2, SC
i2020WR	7-Day	2H/2C	Y	Hardwired	Y	N	RC, RH, C, W1/O/B, W2, Y1, Y2, G, S1, S2, SC
i3020WR	7-Day	3H/2C	Y	Hardwired	Y	N	RC, RH, C, W1/O/B, W2, AUX, Y1, Y2, G, S1, S2, SC

i3 Humidity Control Thermostats


P/N	PROGRAM	STAGES	HP	POWER	WI-FI	HUMIDITY	TERMINATIONS*
i1010HR	7-Day	1H/1C	Y	Dual	N	Y	RC, RH, C, W1/O/B, AUX, Y1, G, S1, S2, SC
i2010HR	7-Day	2H/1C	Y	Dual	N	Y	RC, RH, C, W1/O/B, W2, AUX, Y1, G, S1, S2, SC
i2020HR	7-Day	2H/2C	Y	Dual	N	Y	RC, RH, C, W1/O/B, W2, AUX, Y1, Y2, G, S1, S2, SC

i3 Wi-Fi & Humidity Control Thermostats

P/N	PROGRAM	STAGES	HP	POWER	WI-FI	HUMIDITY	TERMINATIONS*
i1010WHR	7-Day	1H/1C	Y	Hardwired	Y	Y	RC, RH, C, W1/O/B, AUX, Y1, G, S1, S2, SC
i2010WHR	7-Day	2H/1C	Y	Hardwired	Y	Y	RC, RH, C, W1/O/B, W2, AUX, Y1, G, S1, S2, SC
i2020WHR	7-Day	2H/2C	Y	Hardwired	Y	Y	RC, RH, C, W1/O/B, W2, AUX, Y1, Y2, G, S1, S2, SC

* Includes AUX output that is software configurable for humidification or dehumidification applications.

Dimensions



Specifications subject to change without notice.

Specifications:

- 6 (1A) relay outputs
- 7-Day, 5-2-Day, or 5-1-1 day programmable
- Configurable for multiple systems
- Large display with backlight
- Selectable Fahrenheit or Celsius
- Icon indicator lights
- Relay outputs – minimum voltage drop in thermostat
- Remote sensor compatible
- Ideally suited for:
 - Residential (new construction/replacement)
 - Light commercial
- Works with two-transformer systems

Typical Applications:

- Temperature controls in residential and commercial buildings
- Appliances such as heating, air conditioning, and refrigeration equipment including commercial freezers

