

SENTRY 3N1

DISCONNECT WITH INTERNAL VOLTAGE MONITORING AND SURGE PROTECTION

Protects against:

**OVER
UNDER
VOLTAGE**

**HIGH
POWER
SURGES**


**RAPID
SHORT
CYCLING**

SENTRY 3N1



- All components pre-wired for 208/240VAC
- Easy to view, backlit digital display
- Surge protection device pre-wired and mounted inside the enclosure
- Easy installation and set-up
- On-board 40amp contactor rated for inductive loads
- Includes a 40amp breaker

RSH-50VRMDC KIT



Feature	ICM Offers	RectorSeal Offers
Operating Voltage	208/240 VAC, 1-Ph, 50/60 Hz	120/240 VAC, 1-Ph, 50/60 Hz
On-board Contactor for Inductive Loads	Yes	No
Output Rating	40AMP Contactor (Non-latching secondary safety feature)	60AMP Magnetic Latching Relay
Breaker Included	40AMP	60AMP
Maximum Surge Capacity	100,000 amps	50,000 amps
TMOV Technology	Yes	Yes
Surge Suppressor Inside Metal Enclosure	Yes	No
Product Enclosure	NEMA 4X/IP66	NEMA 3R/IP66
Protection Modes	L-L, L-G	L-L, L-G
Fault History	Yes	Yes
Backlit LCD Display	Yes	No
Assembly Required Prior to Installation	No	No
Field Programmable	Yes	Yes
Made in America	Yes	No