

SENTRY 3N1

DISCONNECT WITH INTERNAL VOLTAGE MONITORING AND SURGE PROTECTION

Protects against:

**OVER
UNDER
VOLTAGE**

**HIGH
POWER
SURGES**

**RAPID
SHORT
CYCLING**

SENTRY 3N1



- All components pre-wired for 208/240VAC
- Easy to view, backlit digital display
- Surge protection device pre-wired and mounted inside the enclosure
- Easy installation and set-up
- On-board 40amp contactor rated for inductive loads
- Includes a 40amp breaker

RSH-50VRMDC KIT



<i>Feature</i>	<i>ICM Offers</i>	<i>RectorSeal Offers</i>
Operating Voltage	208/240 VAC, 1-Ph, 50/60 Hz	120/240 VAC, 1-Ph, 50/60 Hz
On-board Contactor for Inductive Loads	Yes	No
Output Rating	40AMP Contactor (Non-latching secondary safety feature)	60AMP Magnetic Latching Relay
Breaker Included	40AMP	60AMP
Maximum Surge Capacity	60,000 amps	50,000 amps
TMOV Technology	Yes	Yes
Product Enclosure	NEMA 4X/IP66	NEMA 3R/IP66
Protection Modes	L-L, L-G	L-L, L-G
Fault History	Yes	Yes
Backlit LCD Display	Yes	No
Assembly Required Prior to Installation	No	No
Field Programmable	Yes	Yes
Innovated and Designed in USA	Yes	No
Connected Equipment Warranty	\$25,000	\$5,000